

INSTALLATION INSTRUCTIONS



1. Remove 23.6" of downspout from where the Clean Rain™ is to be situated. Ensure all edges are clean and smooth.
2. Using the quick release tabs remove the Clean Shield™ by lifting it up and out.
3. Fit the correct downspout adaptor to the bottom of the Clean Rain™.
4. Install the Clean Rain™ by sliding it up behind the top section of cut downspout and then down into position. The Clean Rain™ should be slid firmly onto the bottom downspout until it can be pushed no further.
5. Screw the top of the Clean Rain™ in position through the screw slots provided. Ensure appropriate screws and anchors (if required) are used.
6. Insert the Clean Shield™ back into the Clean Rain™. Ensure the Clean Shield™ is sitting firmly in place and check installation is secure.



ON/OFF

The Clean Rain™ can be turned off so that no water is diverted. To do this simply flick the switch on the front of the Clean Rain™ and in the next rainfall event all water will be diverted to stormwater.

MAINTENANCE

The Clean Rain™ is mostly self-cleaning, however it may require occasional maintenance in order to keep it functioning optimally.

RAIN HEAD – Simply lift the Clean Shield™ out by taking hold of the quick release tabs and pull the Clean Shield™ screen upwards and outwards, then hose or brush off any debris.

OUTLET – The outlet has an internal mosquito barrier that prevents any mosquitoes from entering the tank. To clean simply remove the outlet by holding the unit in one hand and with a firm pull remove the outlet adaptor. The mosquito barrier sits within the outlet and can be removed by hand.

FIRST FLUSH – The Smart Sense™ valve may require the occasional clean to remove any build-up of sediment. To clean remove the Clean Rain™ from the wall and take the bottom adaptor off the unit. To maintain optimum performance the washers based at the bottom of the Smart Sense™ valve should be replaced approximately every 12 to 24 months.

Please register your Clean Rain™ product online at www.rainharvesting.com for your replacement reminder.

