

Solar Slowpump



Output: 0.5 – 4 GPM (1 – 15 LPM)

Total Dynamic Lift: Up to 450 ft. (140m)

Suction Capacity: 20 vertical feet (6 m) at sea level. Subtract 1ft. for every 1000ft. altitude (1 m for every 1000 m)

Weight: 16lbs (7kg)

Notes: MUST be filtered clean (reference spec. sheet); 15 – 20 year life expectancy

Warranty: 1 year against defects in materials and workmanship

For details, refer to spec sheet

Flowlight Booster Pumps



Output: 3 – 5 GPM (11-19 LPM)

Total Dynamic Lift: 65 PSI (4.6 kg/sq cm)

Suction Capacity: Low Speed model: 20 vertical feet (6 m) at sea level. Subtract 1 ft. for every 1,000 ft. altitude (1 m for every 1,000 m) Standard model: 10 vertical feet (3 m) at sea level. Subtract 1 ft. for every 1,000 ft. altitude (1 m for every 1,000 m)

Weight: 15 lbs (7 kg)

Notes: MUST be filtered clean (reference spec. sheet);

15 – 20 year life expectancy

Warranty: 1 year against defects in materials and workmanship

For details, refer to spec sheet

SunCentric



Output: 5 – 70 GPM (19 – 265 LPM)

Total Dynamic Lift: Up to 90 ft. (27m)

Suction Capacity: 10 vertical feet (3m) at sea level. Subtract 1ft. for every 1000ft. altitude (1 m for every 1000 m)

Weight: 49 – 70 lbs (23-32 kg) depending on the model

Notes: Does not require filtration – tolerant of dirt; NOT for pressurized applications; no routine maintenance required

Warranty: 2 years against defects in materials and workmanship

For details, refer to spec sheet

Solar Force Piston Pump



Output: 5 – 9 GPM (19 – 34 LPM)

Total Dynamic Lift: Up to 230 ft. (70m) or 100 PSI (6.7 kg/sq cm)

Suction Capacity: 25 vertical feet (7.6m) at sea level. Subtract 1ft. for every 1000ft. altitude (1 m for every 1000 m)

Weight: 115 lbs (53 kg)

Notes: 20-year life expectancy with 5-10 year maintenance intervals;
Tolerant of dirt and dry run

Warranty: 2 years against material defects and workmanship

For details, refer to spec sheet

Solaram Surface Pumps



Output: 2.5 – 9 GPM (11 – 34 LPM)

Total Dynamic Lift: Up to 960 ft. (292m)

Suction Capacity: 25 vertical feet (7.6 m) at sea level. Subtract 1 ft. for every 1,000 ft. altitude (1 m for every 1,000 m)

Weight: 150 lbs (68 kg)

Notes: Great for high-lift applications; 20 year life expectancy; Tolerant of dirt and dry run

Warranty: 1 year against defects in materials and workmanship

[View Spec Sheet](#)

Solar Surface Pumps Accessories

Replacement Pump Heads

Replacement Motors

Dry Run Switch

10 inch Filter Assembly Kit

30 inch Filter Assembly Kit

Float Switch Kits

Replacement Filter Cartridges

Seal and Gasket Kits for SunCentric Pumps

Replacement Brushes

Parts Kits for Solar Force Piston Pumps

Linear Current Boosters (LCBs)

EZ Installation Kit

Foot Valve

Flex Tube Kit for Flowlight Booster Pumps

Note: please refer to the spec. sheets for more details on which accessories apply for your specific application.