

The CLASSIC now ships with the Whizbang Jr. giving you an advanced full featured battery STATE OF CHARGE meter!

With the addition of the Whizbang Jr. to the Classic you now get our State Of Charge (SOC) meter with an accurate SOC percentage on the Classic, as well as features like Amp Hours remaining in the battery. The benefits of having the charge controller do the State Of Charge is knowing exactly when the battery is full based on End Amps and Absorb time, as well as being able to compensate for temperature on the battery capacity. The Whizbang Jr. is easily installed, attaching to the battery shunt and wiring directly into the Classic with a single wire.

Our FREE Local Application software supports SOC monitoring on your Android, iPhone, Windows or Mac PC allowing unprecedented remote system monitoring and system control.

Cell Phone & Local Application display with State Of Charge

Classic 150V (rev 4)

Legacy P&O (On)
Charge Status: BULK MPPT

AUX

AUX 1: VENT FAN HIGH (Auto)(Off)
AUX 2: WHIZBANG JR (On)(Off)

Whizbang Jr.

System: - 2.5A Net Ah: -47Ah

Remaining Ah: 326Ah

SOC: 86%

Temperature:

FET: 30.8°C PCB: 43.3°C

BAT: 20.7°C

Cell Phone Application with State Of Charge



Classic display showing State Of Charge



Whizbang Jr. - Actual Size

