



400 Series

403D-11G

Diesel Engine - ElectropaK

9.2 kWm @ 1500 rev/min
11.4 kWm @ 1800 rev/min
18.1 kWm @ 3000 rev/min



The 400 Series engine family continues to set new standards in the compact engine market. Developed alongside customers to fulfill their needs in the Genset, Compressor, Agricultural and general Industrial markets.

These new ElectropaKs provide compact power, from a robust family of 3 and 4 cylinder diesel engines designed to provide economic and durable operation at Prime and Standby duties, hitting the key power nodes required by the power generation industry.

Powered by your needs

- The 403D-11G ElectropaK is a powerful but quiet 1.1 litre naturally aspirated 3-cylinder compact package

Compact, Clean, Efficient Power

- Design features on the 400D range of ElectropaKs ensures clean rapid starting in all conditions whilst delivering impressive performance with low operating costs in a small, efficient package size

Lower Operating Costs

- Approved for operation on biodiesel* concentrations of up to 20%.
- Oil and filter changes are 500 hours, dependent on load factor.
- Engine durability and reliability, the warranty offering and ease of installation combine to drive down the cost of ownership.

Long-term Power Solution

- The 400D range of ElectropaKs has been designed to fully comply with stringent EU and EPA emissions regulations, providing an emissions compliant power solution for the future (see 'Perkins Emissions Statement' on page 2).

World-class Product Support

- Through an experienced global network of distributors and dealers, fully trained engine experts deliver total service support around the clock, 365 days a year. They have a comprehensive suite of web based tools at their finger tips, covering technical information, parts identification and ordering systems, all dedicated to maximising the productivity of your engine.
- Perkins actively pursues product support excellence by insisting our distribution network invest in their territory to provide you with a consistent quality of support across the globe.
- Throughout the entire life of a Perkins engine, we provide access to genuine OE specification parts giving 100% reassurance that you receive the very best in terms of quality for lowest possible cost... wherever your Perkins powered machine is operating in the world.

Engine Speed	Type of Operation	Typical Generator Output (Net)		Engine Power				Low Idle
				Gross		Net		
		kVA	kWe	kWm	bhp	kWm	bhp	
1500	Prime Power	9.0	7.2	8.6	11.5	8.4	11.3	n/a
	Standby Power	9.9	7.9	9.5	12.7	9.2	12.4	n/a
1800	Prime Power	11.3	9.0	10.7	14.3	10.4	13.9	n/a
	Standby Power	12.4	9.9	11.8	15.8	11.4	15.3	n/a
†3000	Prime Power	17.7	14.2	17.9	24.0	16.5	22.1	1600 ± 25
	Standby Power	19.5	15.6	19.7	26.4	18.1	24.3	1600 ± 25

*Subject to conformance with ASTM D6751 and EN14214.

† Regarding gen sets ≥ 3000 rev/min: 'The U.S. EPA has certified this engine as a **constant speed** engine, with engine speed controlled by a solenoid that allows operation only at idle or full power position. The solenoid is a required element of design. **It is the responsibility of the equipment manufacturer to install the proper solenoid.** Installation of this engine in equipment without the required solenoid (or in any manner that allows variable speed operation) is not covered by EPA certification, voids the emissions warranty, and may subject the equipment manufacturer to penalties under U.S. law'.

The above ratings represent the engine performance capabilities to conditions specified in ISO 8528/1, ISO 3046/1:1986, BS 5514/1. Derating may be required for conditions outside these; consult Perkins Engines Company Limited. Generator powers are typical and are based on typical alternator efficiencies and a power factor (cos θ) of 0.8. Fuel specification: BS 2869: Part 2 1998 Class A2 or ASTM D975 D2.

Rating Definitions: Prime Power: Power available at variable load in lieu of a main power network. Overload of 10% is permitted for 1 hour in every 12 hours operation. Standby (maximum): Power available at variable load in the event of a main power network failure. No overload is permitted. Photographs are for illustrative purposes only and may not reflect final specification.

400 Series

403D-11G

Standard ElectropaK Specification

Air Inlet

- Mounted air filter

Fuel System

- Mechanically governed cassette type fuel injection pump
- Split element fuel filter

Lubrication System

- Wet steel sump with filler and dipstick
- Spin-on full-flow lub oil filter

Cooling System

- Thermostatically-controlled system with belt driven coolant pump and pusher fan
- Mounted radiator, piping and guards

Electrical Equipment

- 12 volt starter motor and 12 volt 15 amp alternator with DC output
- Oil pressure and coolant temperature switches
- 12 volt shut-off solenoid energised to run
- Glow plug cold start aid and heater/starter switch

Flywheel and Housing

- 1500/1800 rev/min
High inertia flywheel to SAE J620 Size 6½ Heavy
Flywheel housing SAE 5 Long
- 3000 rev/min
High inertia flywheel to SAE J620 Size 6½ Light
Flywheel housing SAE 5 Short

Mountings

- Front and rear engine mounting brackets

Optional Equipment


- Workshop manual
- Parts book

Option Groups

A selection of optional items is available to enable you to prepare a specification precisely matched to your needs.

Emissions Statement

- **Constant Speed Engines** for use in Industrial, IOPU and ElectropaK applications: Certified against the requirements of EU Stage IIIA (Directives 97/68/EC, as last amended, for mobile applications); and US EPA Tier 4 Interim (40 CFR Parts 60 for stationary applications and 40CFR Part 1039 for mobile applications).



Fuel Consumption		
Engine Speed	g/kwh	l/hr
	Standby	268
Prime power	248	3.0
75% of prime power	257	2.3
50% of prime power	280	1.7

General Data

Number of cylinders	3
Cylinder arrangement	Vertical in-line
Cycle	4 stroke
Aspiration	Naturally aspirated
Combustion system	Indirect injection
Compression ratio	23:01
Bore and Stroke	77 x 81 mm
Displacement	1.131 litres
Direction of rotation	Anti-clockwise viewed on flywheel
Cooling system	Water cooled
Total coolant capacity	5.2 litres
Total lubrication system capacity	4.9 litres
Length	778 mm
Width	438 mm
Height	730 mm
Total weight (dry)	129.2 kg

Final weight and dimensions will depend on completed specification.



Perkins Engines Company Limited

Peterborough PE1 5NA
United Kingdom
Telephone +44 (0)1733 583000
Fax +44 (0)1733 582240
www.perkins.com

All information in this document is substantially correct at time of printing and may be altered subsequently
Publication No. 1910/01/10 Produced in England ©2008 Perkins Engines Company Limited

Distributed by

Aurora Generators Inc.
16 Industrial Parkway South
Aurora Ontario Canada L4G 0R4
1-877-510-6807
Canada & USA